

EOS



R150S

Lightweight, Fully Stabilised, 12.7mm capable
Remote Weapon Station



R150S



COUNTER UAS (CUAS) SOLUTIONS

Either standalone or as part of EOS' end-to-end CUAS solution suites

UNMANNED LETHALITY SOLUTIONS

Lightweight UGV solutions and containerisation options available



SELF-PROTECTION*

High-end optics and a high rate of long-range, accurate firepower, ensuring crew situational awareness and safety

SPECIFICATIONS	7.62 MM GPMG	M134D 7.62 MM CHAIN GUN	12.7 MM HMG
Height above roof	560 mm/22 in (weapon lowered)		
Weight above roof (incl. weapon & max. ammunition)	124 kg/272 lbs	156 kg/344 lbs	157 kg/446 lbs
Weight below roof – Control Group	27 kg/59 lbs		
Max. ammunition load	550 rds	Up to 1000 rds	200 rds
Elevation/depression	-20° to +60°		
Sweep radius	0.5 m	0.8 m	1.0 m
Firing stability	<1 mrad		

SENSOR UNIT	DAY CAMERA	THERMAL IMAGER
Detection range	>12,000 m	>13,700 m
Recognition range	>5600 m	>5100 m
Identification range	>4700 m	>4000 m

FOR MORE INFORMATION:

CALL +61 2 6222 7900
EMAIL ENQUIRY@EOS-AUS.COM
VISIT EOS-AUS.COM/DEFENCE

*An older model may be shown